


Towards deriving automated implementation & verification mechanisms from a single machine-readable requirements specification

Using Windows Hardening as proof-of-concept

presented @NIST SCAP v2 Workshop April 30th to May 2nd 2019

Patrick Stöckle, Technical University of Munich | Chair of Software and Systems Engineering

Status Quo for almost all SCAP Baselines (with some OpenScap baselines as notable exception)




Implementations and checks are created **and maintained** independently from each other
Implementations not part of SCAP content authoring/maintenance

- Is the implementation valid? Right GPO path, etc.
- Is the check really verifying the implementation?

Relation Implementation ↔ Check is not clear


Status Quo for almost all SCAP Baselines (with some OpenScap baselines as notable exception)

```
<Rule id="SV-88239r1_rule" severity="medium" weight="10.0">
<version>WN16-CC-000410</version>
<title>Remote Desktop Services must be configured with the client connection encryption set to High
Level.</title>
<fixtext fixref="F-80025r1_fix">Configure the policy value for Computer Configuration &gt;&gt;
Administrative Templates &gt;&gt; Windows Components &gt;&gt; Remote Desktop Services &gt;&gt; Remote
Desktop Session Host &gt;&gt; Security &gt;&gt; "Set client connection encryption level" to "Enabled" with
"High Level" selected
</fixtext>
</Rule>
```



Example: IASE Microsoft Windows Server 2016 STIG Benchmark

Goal



DevOps in Baseline Maintenance:

- **Automated Validation**
 - Does this GPO path exist?
(If not, show alternative candidates)
 - Are the parameter values specified in the guidelines valid?
(If not, show possible candidates)
- **Automated Testing:**
 - Execute implementation on test-system
 - Check test results before and after
 - ...


Integration of Hardening in DevOps:

- Derive and use environment/system-specific implementation/check mechanisms
- Support systematic testing via rule-by-rule implementation rather than all-or-nothing implementation
- ...

Our Proof-of-Concept for Windows Hardening



```
/implementations/0/description  
Configure the policy value for Computer Configuration >>  
Administrative Templates >> Windows Components >>  
Remote Desktop Services >> Remote Desktop Session Host  
>> Security >> "Set client connection encryption level" to  
"Enabled" with "High Level" selected.  
  
implementations:  
- relative_id: F-80025r1  
  description: <see below>  
  automations:  
    - system:  
      org.scapolite.implementation.win_gpo  
        ui_path: Computer Configuration \  
Administrative Templates \ Windows Components \  
Remote Desktop Services \ Remote Desktop  
Session Host \ Security \ Set client  
connection encryption level  
  
value: High Level
```



(*) Underlying PowerShell library can be used to

- Implement one rule
- Implement all rules
- Check one rule
- Check all rules

Example

```
## /implementations/0/description
Configure the policy value for Computer Configuration >> Administrative Templates >> Windows Components >> Remote Desktop Services >> Remote Desktop Session Host >> Security >> "Set client connection encryption level" to "Enabled" with "High Level" selected.
```

```
ui_path: Computer Configuration \ Administrative Templates \ Windows Components \ Remote Desktop Services \ Remote Desktop Session Host \ Security \ Set client connection encryption level
value: High Level
verification_status: Checked.
```

```
config: Computer
registry_key: SOFTWARE\Policies\Microsoft\Windows NT\Terminal Services
value_name: MinEncryptionLevel
action: DWORD:3
```

Registry Automation

```
string_value: Success
guid: '{0CCE923F-69AE-11D9-BED3-505054503030}'
name: Credential Validation
value: 1
```

„audit.csv“ Automation

```
setting_name: SeAuditPrivilege
section: Privilege Rights
value:
- '*S-1-5-19'
- '*S-1-5-20'
```

„INF-File“ Automation

Example automations for other GPO settings

Verification

```
ui_path: Computer Configuration \ Administrative Templates \ Windows Components \ Remote Desktop Services \ Remote Desktop Session Host \ Security \ Set client connection encryption level
value: High Level
verification_status: Unchecked.
error_hint: The policy Computer Configuration \ Administrative Templates \ Windows Components \ Remote Desktop Services \ Remote Desktop Session Host \ Security \ Set client connection encryption was not found, but there were 2 similar policies.
If the UI path you were looking for is in the array, please replace the original UI path with the new UI path.
candidates:
- Windows Components \ Remote Desktop Services \ Remote Desktop Session Host \ Security \ Set client connection encryption level
- Windows Components \ Remote Desktop Services \ Remote Desktop Session Host \ Security \ Require secure RPC communication
```

```
ui_path: Computer Configuration \ Administrative Templates \ Windows Components \ Remote Desktop Services \ Remote Desktop Session Host \ Security \ Set client connection encryption level
value: High
verification_status: Unchecked.
error_hint: To apply this rule, please choose a setting value for each sub-setting in candidates. Next, replace the content of the 'value' attribute with the content of candidates.
candidates:
- Low Level
- Disabled
- High Level
- Client Compatible
```

Conclusion

- As consumers of CIS and IASE Windows baselines, what we do now is to
 - Use natural language processing to turn human-readable specifications of GPO settings into machine-readable specifications (86.5% fully automated, 13.5% require manual intervention)
 - Use machine-readable implementations to generate required artefacts for DevOps approaches both in maintaining and using security baselines
- What we would like to do:
 - Have CIS/IASE ... specify required GPO settings in machine-readable way
 - Use these machine-readable GPO settings
- As users of SCAP, what we would like is to shift focus a little more on automated implementation than is currently the case
 - our Windows PoC shows that it is possible for certain systems;
 - including machine readable fix elements for Windows GPO settings is possible in SCAP as it is, we just need to agree on a definition for the „fix“ system.
- Other systems will be harder to tackle, but for usage of SCAP(v2) in DevSecOps, there is no other way: we need machine-readable specifications of required security configurations.

Contact

Patrick Stöckle

Patrick.Stoeckle@tum.de

<http://www22.in.tum.de/stoeckle/>

www.linkedin.com/in/patrick-stoeckle

