



Datacryptor® Gig Ethernet and 10 Gig Ethernet

FIPS 140-2 Level 3 Security Policy

Firmware Version v4.5 (with Point-to-Point license)

Hardware Versions

| | |
|-------------------------------|------------------------------------------------------|
| <i>Gig Ethernet</i> | <i>1600X433 Rev. 01, 1600X433 Rev. 02</i> |
| <i>10 Gig Ethernet</i> | <i>1600X437 Rev. 01, 1600X437 Rev 02</i> |

CONTENTS

| | |
|--------------------------------------------------------------|----|
| 1. INTRODUCTION..... | 4 |
| 2. IDENTIFICATION AND AUTHENTICATION POLICY | 11 |
| 2.1 Crypto-Officer Role | 11 |
| 2.2 User Role..... | 11 |
| 2.3 Authentication | 12 |
| 3. ACCESS CONTROL POLICY..... | 13 |
| 3.1 Roles and Services..... | 13 |
| 3.2 Cryptographic Keys, CSPs and Access Rights..... | 15 |
| 3.3 Zeroisation | 17 |
| 3.4 Other Security-Relevant Information..... | 17 |
| 4. PHYSICAL SECURITY POLICY | 19 |
| 4.1 Inspection/Testing of Physical Security Mechanisms | 19 |
| 4.1.1 1600X433, Rev. 01 Hardware | 19 |
| 4.1.2 1600X433, Rev. 02 Hardware | 20 |
| 4.1.3 1600X437, Rev. 01 Hardware | 21 |
| 4.1.4 1600X437, Rev. 02 Hardware | 23 |
| 5. MITIGATION OF OTHER ATTACKS POLICY..... | 25 |
| ACRONYMS AND ABBREVIATIONS..... | 26 |
| REFERENCES..... | 27 |

Tables

| | |
|----------------------------------------------------------------------|----|
| Table 1-1 Physical Ports and Status Indicators..... | 7 |
| Table 1-2 Physical Port to Logical Port Mapping | 7 |
| Table 1-3 Power-Up Tests | 9 |
| Table 1-4 Conditional Tests | 10 |
| Table 2-1 Roles and Required Identification and Authentication | 12 |
| Table 2-2 Strengths of Authentication Mechanisms..... | 12 |
| Table 3-1 Services Authorized for Crypto Officer..... | 13 |
| Table 3-2 Services Authorized for User | 15 |
| Table 3-3 Cryptographic Keys and CSPs..... | 15 |

THALES e-SECURITY

DATACRYPTOR® GIG ETHERNET
SECURITY POLICY

Figures

| | |
|------------------------------------------------------------------------------------|----|
| Figure 1-1 Datacryptor® Ethernet Crypto Module Example Network Configuration | 5 |
| Figure 4-1 1600X433, Rev. 01 Front..... | 19 |
| Figure 4-2 1600X433, Rev. 01 Rear | 19 |
| Figure 4-3 1600x433, Rev. 01 Top..... | 20 |
| Figure 4-4 1600X433, Rev. 02 Front..... | 20 |
| Figure 4-5 1600X433, Rev. 02 Rear | 20 |
| Figure 4-6 1600x433, Rev. 02 Top..... | 21 |
| Figure 4-7 1600X437, Rev. 01 Front..... | 21 |
| Figure 4-8 1600X437, Rev. 01 Rear | 22 |
| Figure 4-9 1600x437, Rev. 01 Top..... | 22 |
| Figure 4-10 1600X437, Rev. 02 Front..... | 23 |
| Figure 4-11 1600X437, Rev. 02 Rear | 23 |
| Figure 4-12 1600x437, Rev. 02 Top..... | 24 |

DATACRYPTOR® GIG ETHERNET SECURITY POLICY

1. INTRODUCTION

Thales e-Security is a global leader in the network security market with over 60,000 network security devices in operation, being one of the first companies to introduce a link encryption product to the market in the early 1980s.

The Datacryptor® family represents Thales' next generation of network security devices for a wide variety of communications environments. It is the culmination of 20 years experience protecting wide-area and point-to-point networks for governments, financial institutions and information-critical industries worldwide.

This document is the Security Policy¹ for the Thales e-Security Datacryptor® Gig Ethernet, conforming to the FIPS140-2 Security Policy Requirements [1]. This Security Policy applies to the Datacryptor® Gig Ethernet when operated in Point-to-Point mode with the corresponding license.

Further information on the Datacryptor® family and the functionality provided by the Datacryptor® Gig Ethernet is available from the Thales web site: <http://iss.thalesgroup.com>

Overview

The Datacryptor® Gig Ethernet is a multi-chip standalone cryptographic module which facilitates secure data transmission across Ethernet networks at 1 Gb/s or 10Gb/s.

Operating at primarily at OSI Layer 2, the Data Link Layer of the protocol stack the Datacryptor® Gig Ethernet is targeted at high speed/high data throughput applications between telecommunication facilities introducing virtually no overhead or latency to the network. Unlike Layer 3 IP security devices (IPSEC) the Datacryptor® Gig Ethernet is independent of network configurations resulting in a solution that is simple and inexpensive to manage.

As a solution for high speed/high-bandwidth data transport over LANs and WANs, the Datacryptor® Gig Ethernet enables customers to take advantage of the most cost effective transport services available while ensuring the confidentiality of the information carried through these connections.

The Datacryptor® Gig Ethernet uses the strongest commercially available and government approved cryptography. It is designed to easily fit into a variety of network configurations supporting multiple modes of operation including bulk, tunnel and Virtual LAN (VLAN).

This Security Policy defines the Datacryptor® Gig Ethernet cryptographic module for two hardware versions, 1600X433 (low speed module) which utilizes a Xilinx VirtexII-Pro XC2VP30 FPGA and supports data transmission at 1Gb/s and 1600X437 (high speed module) which utilizes two Xilinx VirtexII-Pro XC2VP50 FPGAs and supports data transmission at 10Gb/s. These variants utilize a different hardware platform but are functionally identical therefore all references to Datacryptor® Gig Ethernet or module refer to both variants unless explicitly stated otherwise.

Figure 1-1 shows a typical Datacryptor® Gig Ethernet configuration where 2 LANs are securely linked across a public domain Ethernet network.

¹ This document is non-proprietary and may be reproduced freely in its entirety but not modified or used for purposes other than that intended.

DATACRYPTOR® GIG ETHERNET SECURITY POLICY


Modes of Operation

The Datacryptor® Gig Ethernet can only operate in an FIPS 140-2 Approved mode (this includes cryptographic services and bypass services). The modes of operation are detailed below:

- **Standby Mode** The module transmits/receives no data via either its Host or Network interfaces on that channel. This mode is automatically entered if the module detects an error state or at start-up. This mode is indicated by the flashing green Encrypt LED.
- **Plain Text Mode²** All data received through the Host interface on that channel is transmitted through the Network interface as plain text. Similarly, all data received through the Network interface on that channel is transmitted through the Host interface with no decryption applied. This mode should only be used for diagnostic purposes, or if there is no security risk to the data if it is transferred unencrypted. This mode is indicated by the solid red Plain LED. The module does not support an alternating plaintext mode.
- **Encrypt Mode** All data received through the Host interface on that channel is encrypted using the transmit Data Encryption Key (DEK) and then the encrypted data is transmitted through the Network interface. Similarly, all data received through the Network interface on that channel is decrypted using the receive DEK and then the decrypted data is transmitted through the Host interface. This mode is indicated by the solid green Encrypt LED.

The mode of operation is selectable by the Crypto Officer using the Secure Remote Management facility and the current mode of operation is displayed using both the Front Panel LEDs and the Secure Remote Management (Element Manager PC) facility. Refer to the User Manual [3] for further details.

Figure 1-1 Datacryptor® Ethernet Crypto Module Example Network Configuration



² This is the bypass mode.

Physical Ports

Both variants of the Datacryptor® Gig Ethernet provide the same set of physical ports with the exception of the host and network line interfaces, which use Small Form Factor Pluggable (SFP) for low speed modules and 10 Gigabit Small Form Factor Pluggable (XFP) for high speed modules

The physical ports are described below in Table 1-1 Physical Ports and Status Indicators:

DATACRYPTOR® GIG ETHERNET SECURITY POLICY

Table 1-1 Physical Ports and Status Indicators

| Port | Description |
|---------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Network | Connects to the public network for sending and receiving encrypted user data and inter-module key exchange data. |
| Host | Connects to the private network for sending and receiving plaintext user data. |
| RS-232 | Connects to a local terminal for initialization of the module and also allows remote management from the Element Manager application utilizing the Point-to-Point (PPP) protocol. |
| Ethernet | Allows the remote management of a unit using the Element Manager application and status report using an SNMP management application. |
| Front Panel LEDs | Indicates the operational state of the unit, including Alarm state, Error state, Plain or Encrypt mode and Host and Network line status. |
| Line Interface LEDs | Indicates module present and laser input detected. |
| PSU LEDs | Indicates the status of the PSUs (powered/unpowered) |
| Power | Dual redundant power interface supporting customer options of AC or DC and international power cord standards. |

The physical ports are mapped to four logical ports defined by FIPS 140-2 as described below in Table 1-2 Physical Port to Logical Port Mapping:

Table 1-2 Physical Port to Logical Port Mapping

| Logical Interface | Description and Mapping to Physical Port |
|-------------------|-----------------------------------------------------------------------------------------------|
| Data Input | Host Line Interface Network Line Interface |
| Data Output | Host Line Interface Network Line Interface |
| Control | RS-232 Interface Ethernet Interface |
| Status | RS-232 Interface Ethernet Interface Front Panel LEDs Line Interface LEDs PSU LEDs |

DATACRYPTOR® GIG ETHERNET SECURITY POLICY

User Data Security

The communications channel between two Datacryptor® Gig Ethernets is assumed to be vulnerable and therefore the Datacryptor® Gig Ethernet encrypts the entire user data stream³.

The Datacryptor® Gig Ethernet uses public key cryptography for authentication and key agreement⁴ and symmetric key cryptographic for data confidentiality. The authentication mechanism employs signed X.509 v3 certificates using the Digital Signature Algorithm (DSA) for signature verification. The Diffie-Hellman protocol is used to establish a Key Encryption Key (KEK) between modules. Data Encryption Keys (DEKs), used for encrypting and decrypting data traffic, are derived from the KEK.

Random Number Generation

The Random Number Generator consists of a hardware random number source providing a seed key to a FIPS 186-2 Appendix 3.1 [2] Approved pseudo random number generator.

The RNG is used in the generation of private and secret keys including Diffie-Hellman static/ephemeral and Data Encryption Keys.

Algorithm Support

The Datacryptor® Gig Ethernet contains the following algorithms:

- AES-256 for data encryption
- DSA for signature verification
- SHA-1 hashing algorithm
- Diffie-Hellman for key agreement

Physical Security

The multi-chip standalone embodiment of the circuitry within the Datacryptor® Gig Ethernet is contained within a strong metal production-grade enclosure that is opaque within the visible spectrum to meet FIPS 140-2 Level 3. The enclosure completely covers the module to restrict unauthorized physical access to the module. The physical security includes measures to provide both tamper evidence and tamper detection and response. In the case of tamper response all sensitive information stored within the module will be zeroised.

The Datacryptor® Gig Ethernet's cryptographic boundary (FIPS 140-2 [1], section 2.1) is the physical extent of its enclosure but excludes the dual redundant power supplies which are external to this boundary and may be hot-swapped by a customer and does not require a "return to factory" operation.

³ Providing the modules are configured to operate in Encrypt mode.

⁴ This key agreement method provides 80-bits of encryption strength.

DATACRYPTOR® GIG ETHERNET SECURITY POLICY

Secure Remote Management

The Datacryptor® Gig Ethernet may be remotely and securely managed using the Element Manager.

The Datacryptor® Gig Ethernet can also be managed (for status only) using an SNMP v3.0 management application. Only one management session is permitted at a time with a Datacryptor® Gig Ethernet.

Diagnostics

A variety of diagnostics are available to maintain secure operation. These diagnostics include cryptographic mechanisms, critical functions and environmental monitoring. In addition the module supports a local loop back mode to aid in diagnosing network connectivity. Log files are maintained in the Datacryptor® Gig Ethernet and can be viewed or printed.

If the Datacryptor® Gig Ethernet is faulty, as indicated by the failure of a self-test diagnostic, it will render itself inoperable until the fault is rectified.

- **Power-Up Tests** On power-up known answer tests (KAT) are performed on all cryptographic algorithms and the pseudo-random number generator. In addition the integrity of all firmware is checked.

Table 1-3 Power-Up Tests

| Function Checked | Description |
|----------------------------------------------------|--------------------------------------------|
| DSA (CA Algorithm) | KAT Test |
| AES-256-S/W (KEK Algorithm) | KAT Test |
| AES-256 – H/W (Traffic Encrypt/Decrypt Algorithm) | KAT Test |
| SHA-1 | KAT Test |
| SHA-1 RNG | KAT Test |
| Firmware Integrity | 16 bit Error Detection Code (EDC) Checksum |

- **Conditional Tests**
 - The output of both the hardware random number generator and the pseudo-random number generator are checked when ever random data is requested by the module. Subsequent random numbers are compared against the last generated value to verify that these values are not the same.
 - The module also performs a bypass test before entering an encrypted channel mode. When switching from a plain to an encrypted channel mode the module issues an encrypted challenge to its peer using the Data Encryption Key (DEK). The challenge is then decrypted by the peer using its DEK, and if verified, an encrypted response is returned to the module (using the DEK). The response is decrypted by the module

DATACRYPTOR® GIG ETHERNET

SECURITY POLICY

(using the DEK) and verified. If successful the channel is established as being in an encrypted state with matching DEKs in each module.

- In the case of a firmware upgrade, this is digitally signed by a CA using DSA allowing the module to verify the image so preventing unauthorized firmware upgrades. After loading firmware onto this module it may no longer be a FIPS 140-2 validated module unless the firmware has been FIPS 140-2 validated. This feature is used as an upgrade path for future FIPS 140-2 approved modules.

Table 1-4 Conditional Tests

| Function Checked | Description |
|---------------------------------|--------------------|
| Hardware RNG | CRNG |
| FIPS186-2 RNG | CRNG |
| Bypass | Bypass Test |
| Firmware Upgrade Authentication | Verify (DSA) |

DATACRYPTOR® GIG ETHERNET SECURITY POLICY

2. IDENTIFICATION AND AUTHENTICATION POLICY

The two roles associated with the Datacryptor® Gig Ethernet are:

- Crypto-Officer** Commissioning and configuration of the Datacryptor® Gig Ethernet.
- User** This role occurs when two Datacryptor® Gig Ethernets are communicating with each other.

The Datacryptor® Gig Ethernet does not support multiple concurrent roles.

2.1 Crypto-Officer Role

The Datacryptor® Gig Ethernet can be managed by the Crypto-Officer using either of the following two methods:

- **Element Manager** - This PC-based software application enables a Crypto-Officer to commission and administer the module.
- **SNMP Management Station** - This is limited to requesting and obtaining status information from the Datacryptor® Gig Ethernet.

The Crypto-Officer role utilizes the Element Manager to commission and configure the module via the dedicated Ethernet or serial management port.

Commissioning a module installs a X.509 certificate (containing the CA public key, certificate name, unit serial number and certificate life time) and the required Diffie Hellman parameters (base and modulus) to allow the Datacryptor® Gig Ethernet to generate a corresponding Diffie Hellman key set. This information is digital signed allowing the unit to authenticate the certificate's signature using the issuing CA Public key held within the module. The module must be commissioned before it may be administered.

When administering the module the Element Manager establishes a secure connection (connection authentication and data confidentiality) to the module. This connection is established and protected in the same manner as a module to module connection. To establish the secure connection the Crypto-Officer uses a removable media key-material set containing the Crypto-Officer's name and access rights, Diffie-Hellman key set and own certificate. To access the key-material set the Crypto-Officer must login to the Element Manager by presenting the key-material set and the Crypto-Officer's own password of at least 8 ASCII printable characters. This allows the Element Manager to verify the identity of a Crypto-Officer before establishing a secure connection using the key material set.

2.2 User Role

The Crypto-Officer can download one or more signed X.509 User Certificates to the Datacryptor® Gig Ethernet. Each User Certificate gives a Datacryptor® Gig Ethernet an identity.

Identity-based authentication is implemented between two communicating Datacryptor® Gig Ethernets. The modules are then operating in the User role. This identity can be authenticated to another module which verifies the User Certificate's signature using the issuing CA Public key held within the module.

DATACRYPTOR® GIG ETHERNET

SECURITY POLICY

If the issuing CA Public key is not held within the authenticating module then verification cannot be undertaken. Therefore no communications channel can be established between the two Datacryptor® Gig Ethernets.

2.3 Authentication

The types and strengths of authentication for each Role identified for the Datacryptor® Gig Ethernet are given in *Table 2-1* and *Table 2-2* below.

Table 2-1 Roles and Required Identification and Authentication

| Role | Type of Authentication | Authentication Data |
|----------------|------------------------|----------------------------------|
| Crypto-Officer | Identity based | Signed X.509 Digital Certificate |
| User | Identity based | Signed X.509 Digital Certificate |

The identity of each entity performing a role that requires authentication is held within the X.509 Digital Certificate allowing the identity and authorization of the operator to be validated by checking the signature (DSA) of the certificate.

Table 2-2 Strengths of Authentication Mechanisms

| Authentication Mechanism | Strength of Mechanism |
|----------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Signed X.509 Digital Certificate | <p>The strength depends upon the size of the private key space. The Datacryptor® Gig Ethernet uses DSA, which is a FIPS Approved algorithm. Therefore the probability of successfully guessing the private key (160 bits), and hence correctly signing an X.509 certificate, is significantly less than one in 1,000,000 (2^{160}).</p> <p>Multiple attempts to use the authentication mechanism during a one-minute period do not constitute a threat for secure operation of the Datacryptor® Gig Ethernet. This is because each attempt requires the Datacryptor® Gig Ethernet to check the signature on the certificate that is to be loaded. Therefore the total number of attempts that can be made in a one-minute period will be limited by the Datacryptor® Gig Ethernet signature verification and response operation, which takes on average approximately 30 seconds. The majority of this time is accounted for by the communications overheads since the signature checking operation within the module is relatively fast.</p> <p>Given the very large size (160 bits) of the private key space used by the FIPS Approved signature algorithm (DSA) loaded in the Datacryptor® Gig Ethernet it follows that the probability that an intruder will be able to guess the private key, and thereby gain authentication, by making multiple attempts is significantly less than one in 100,000 ($2^{160} / 2$).</p> <p>There is no feedback of authentication data to the Crypto-Officer or User that might serve to weaken the authentication mechanism.</p> |

DATACRYPTOR® GIG ETHERNET
SECURITY POLICY

3. ACCESS CONTROL POLICY

3.1 Roles and Services

Table 3-1 Services Authorized for Crypto Officer lists the authorized services available for each role within the Datacryptor® Gig Ethernet. All services require authentication to the module.

For further details of each operation refer to the Datacryptor® Gig Ethernet User Guide [3].

Table 3-1 Services Authorized for Crypto Officer

| Service | Description | Input | Output | Access |
|-----------------------|----------------------------------------------------------------------------------|-----------------------------------------------------------------|-------------------------------------------|---------------------------------------------------------------------------|
| Access module | Login/logout of the module | password, crypto officer public key, crypto officer certificate | Command response | Peer Module Certificate - read |
| Manage Key Material | Loads module's key material, deletes module's key material | module public key, module certificate | Command response | CA Public Key – read/write, Module Certificate – read/write |
| General Configuration | Display/edit module's name, description, time and interface settings. | Commands and parameters | Command response | None |
| Diagnostics | Reboot or erase key material. Configure loopback mode | Commands and parameters | Command response | None |
| IP Management | Display/edit module's ports, Ethernet and serial, configuration. | Commands and parameters | Command response | None |
| SNMP | Display/edit general information, SNMP version, SNMP communities and SNMP traps. | Commands and parameters | Command response | None |
| IP Routes | Display/edit IP routing information | Commands and parameters | Command response | None |
| Security | Display/edit key lifetimes, and general key exchange parameters | Commands and parameters | Command response; key exchange if forced. | Key Encryption Key – write (delete), Data Encryption Key – write (delete) |
| RIP | Display/edit RIP version and RIP password | Commands and parameters | Command response | None |
| Communications | Display/edit Ethernet mode (bulk, tunneling), interface mode | Commands and parameters | Command response | None |
| | | | | |

DATACRYPTOR® GIG ETHERNET

SECURITY POLICY

| Service | Description | Input | Output | Access |
|------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|---------------------------------|---------------------------------------------------------------------------------------------|--------|
| Encryption | Display current connection mode - one of standby, plain or encrypt and ping the connected unit. | Commands and parameters | Command response, ping packet to connected peer. | None |
| Expert (only applicable to 1600X433 module) | Display/edit Cipher Text Stealing mode, enabled or disabled. | Commands and parameters | Command response | |
| Tunneling | Display own MAC address, display/edit peer MAC address, filter rules, VLAN identification and fragmentation size. | Commands and parameters | Command response. | |
| Environment | Display fan speed, module temperature and unit power status. | Commands and parameters | Command response | None |
| License | Display/edit currently loaded license file for the Datacryptor OC-3/12/48C module. | License file | Command Response | None |
| Show Status | View status of the module. | None Commands and parameters | Front Panel LEDs Status Indicators Status information over Element Manager or SNMP Traps | None |
| Operator Callable Self-Test | Module performs self-test | Reboot Module | Front Panel LEDs Status Indicators | None |
| Plaintext | Enable module to perform bypass. | Commands and parameters. | Bypass test pass or fail indicated by Front Panel Status LEDs | None |

DATACRYPTOR® GIG ETHERNET SECURITY POLICY

Table 3-2 Services Authorized for User

| Service | Description | Input | Output | Accessed |
|---------|--------------------------------------------------------------------------------------|--------------------------|--------------------------|------------|
| Encrypt | Encrypt data received from the Host interface and transmit on the Network interface. | User traffic (plain) | User traffic (encrypted) | DEK – read |
| Decrypt | Decrypt data received from the Network interface and transmit on the Host interface. | User traffic (encrypted) | User traffic (plain) | DEK - read |

3.2 Cryptographic Keys, CSPs and Access Rights

The cryptographic keys and CSPs stored in the Datacryptor® Gig Ethernet module are listed in *Table 3-3*.

All private and secret keys (Diffie-Hellman, KEKs and DEKs) are generated internally in the module and may not be either loaded or read by the Crypto Officer or User.

Table 3-3 Cryptographic Keys and CSPs

| Keys/CSPs | Description | KEY/CSP Type and Size | Generated/ Established | Stored | Zeroised |
|---------------|-------------------------------------------------------------------------------------------------|-----------------------|---------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------|---------------------------------------------------------|
| Master Key | Encrypts all non-volatile Keys and CSPs stored on the module. | AES (256 bits) | Generated at start-up if not present using the module's hardware random number generator and an approved RNG (cert# 588). | Battery Backed SRAM (plaintext) | On tamper detect or by user. |
| CA Public Key | The public key of the CA key pair use to verify subsequent key material loaded into the module. | DSA (1024 bits) | Generated external and loaded as part of the commissioning process. | Non-volatile memory – Compact Flash (encrypted) | When the key is deleted or replace by a subsequent key. |

DATACRYPTOR® GIG ETHERNET

SECURITY POLICY

| Keys/CSPs | Description | KEY/CSP Type and Size | Generated/ Established | Stored | Zeroised |
|----------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Own Module Certificate/Diffie-Hellman Static Key Pair | An X.509 certificate containing the module name, Diffie-Hellman static public key (the static private key is stored separately) and associated parameters. | Diffie-Hellman (1024 bits) | The Diffie-Hellman static key pair is generated locally by the module, using the module's hardware random number generator and an approved RNG (cert#588) from the parameters supplied during the commissioning process. The module name and Diffie-Hellman static public key is then exported to be signed by issuing CA so forming the module certificate. | Own Module Certificate Non-volatile memory – Compact Flash (encrypted) Diffie-Hellman static private key – Non-volatile memory – FRAM (encrypted) | When the certificate is deleted or replaced by a subsequent certificate. The Diffie-Hellman static private key may be deleted by a user. |
| Diffie-Hellman Ephemeral Key Pair | The Diffie-Hellman ephemeral key pair. | Diffie-Hellman (1024 bits) | The Diffie-Hellman ephemeral key pair is generated locally by the module, using the module's hardware random number generator and an approved RNG (cert#588) from the parameters supplied during the commissioning process. This key pair is used in conjunction with the static key pair to establish the KEK. | Volatile memory – SRAM (encrypted) | Zeroised when a new link is established. |
| Peer Module Certificate/Diffie-Hellman Static Public Key | Received during link establishment between two modules to allow authentication of the peer module using signature verification (DSA). | Diffie-Hellman (1024 bits) | Generated by peer in the same manner as Own Module Certificate. | Non-Volatile memory – Compact Flash (encrypted) | Zeroised when a new link is established. |
| | | | | | |
| Seed Key | Used by the Approved RNG | RNG Seed Key (256 bits) | Generated via internal hardware RNG | Not stored. | Zeroised when a subsequent seed key is generated and the CRNG comparison is successful. |

DATACRYPTOR® GIG ETHERNET

SECURITY POLICY

| Keys/CSPs | Description | KEY/CSP Type and Size | Generated/ Established | Stored | Zeroised |
|---------------------------------------------|--------------------------------------------------------------------------------------------------------|-----------------------|----------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------|
| Data Encryption Keys (DEKs) | A pair of keys (one for transmit and one for receive) used for encryption and decryption of line data. | AES (256 bits) | Generated during link establishment using AES (KEK), DEKDD and XOR operations. | Volatile memory – BRAM & FRAM (up to three stored with CRC integrity protection) | Zeroised when a new link is established or when a new DEK is generated at a user defined time interval. |
| Data Encryption Key Derivation Data (DEKDD) | Random data used to derive data encryption keys in conjunction with KEK | 256 bits | Generated during DEK derivation using the module's hardware random number generator and an approved RNG (cert# 588). | Not stored. | N/A |
| Key Encryption Key (KEK) | Key used to derive data encryption keys in conjunction with DEKID | AES (256 bits) | Established during link establishment with Diffie-Hellman using the static and ephemeral key pairs. | Volatile memory – BRAM (encrypted) | Zeroised when a new link is established or when a new KEK is generated at a user defined time interval. |

Note: A Thales e-Security public key is embedded within the firmware which is used to verify the integrity of the firmware during module startup.

3.3 Zeroisation

The Crypto Officer can zeroise keys through the Element Manager application. As indicated in the table above, the Crypto Officer has the choice to directly delete keys, establish a new link with another peer module or force the module to generate new keys. Keys that are not zeroised are encrypted by the master key. The module zeroises the master key when the tamper response and zeroisation circuitry responds to an intrusion of the enclosure which renders all other keys indecipherable.

3.4 Other Security-Relevant Information

FIPS Approved Mode of Operation

The Datacryptor® Gig Ethernet only operates in an Approved mode and does not support any unapproved modes of operation.

1. FIPS 140-2 Approved and Certified

- SHA-1 (FIPS Certificate #985)
- DSA (FIPS Certificate #349)
- FIPS 186-2 RNG (FIPS Certificate #588)
- AES-256 (FIPS Certificate #1033, 1079 and 1080)

DATACRYPTOR® GIG ETHERNET

SECURITY POLICY

2. Non-Approved Allowed

- Diffie-Hellman (key agreement; key establishment methodology provides 80 bits of encryption strength).
- Hardware RNG for generating seed key for Approved RNG

Datacryptor® Gig Ethernet FPGA Details

This Security Policy defines the Datacryptor® Gig Ethernet cryptographic module for two hardware versions which utilize different FPGAs as described below:

- 1600X433 Rev. 01 & Rev. 02 (low speed module) utilize a Xilinx VirtexII-Pro XC2VP30 FPGA.
- 1600X437 Rev. 01 & Rev. 02 (high speed module) utilize two Xilinx VirtexII-Pro XC2VP50 FPGAs.

DATACRYPTOR® GIG ETHERNET
SECURITY POLICY

4. PHYSICAL SECURITY POLICY

The Datacryptor® Gig Ethernet is a multiple-chip standalone cryptographic module consisting of production-grade components to meet FIPS 140-2 Level 3.

The Datacryptor® Gig Ethernet is protected by a strong metal production-grade enclosure that is opaque within the visible spectrum with tamper evident labels and tamper response mechanisms. Attempts to access the module without removing the cover will cause visible physical damage to the module and/or tamper evident labels.

The module’s ventilation holes on the sides and back on the enclosure are fitted with baffles to prevent physical probing of the enclosure.

The module has a removable top cover which is protected by tamper response circuitry, which zeroes all plaintext CSPs. Access to the internal components of the module requires that these covers are removed.

The module's cryptographic boundary (FIPS 140-2 [1], section 2.1) is the physical extent of its external casing but excludes the field replaceable dual redundant power supply.

4.1 Inspection/Testing of Physical Security Mechanisms

The following guidelines should be considered when producing a Security Policy for the network in which the module is deployed.

The Datacryptor® Gig Ethernet should be periodically checked by the Crypto Officer for evidence of tampering, in particular damage to the clear tamper evident labels (highlighted in outline red) as these are part of the security of the unit. In addition the audit logs should be checked for activation of the tamper response mechanism.


The frequency of a physical inspection depends on the information being protected and the environment in which the unit is located. At a minimum it would be expected that a physical inspection would be made by the Crypto Officer at least monthly and audit logs daily.

4.1.1 1600X433, Rev. 01 Hardware

Figure 4-1 1600X433, Rev. 01 Front




Figure 4-2 1600X433, Rev. 01 Rear



THALES e-SECURITY

DATACRYPTOR® GIG ETHERNET SECURITY POLICY

Figure 4-3 1600x433, Rev. 01 Top



The tamper evident labels shall only be applied at the Thales facility. Tamper evident labels are not available for order or replacement from Thales.

Four tamper evident labels are required to be visible and undamaged for each module to be operated in a FIPS approved mode of operation. They must be in the positions shown in Figure 4-2 and


Figure 4-3.

4.1.2 1600X433, Rev. 02 Hardware

Figure 4-4 1600X433, Rev. 02 Front



Figure 4-5 1600X433, Rev. 02 Rear




THALES e-SECURITY

DATACRYPTOR® GIG ETHERNET

SECURITY POLICY

Figure 4-6 1600x433, Rev. 02 Top




The tamper evident labels shall only be applied at the Thales facility. Tamper evident labels are not available for order or replacement from Thales.

Two tamper evident labels are required to be visible and undamaged for each module to be operated in a FIPS approved mode of operation. They must be in the positions shown in

Figure 4-6.

4.1.3 1600X437, Rev. 01 Hardware

Figure 4-7 1600X437, Rev. 01 Front



THALES e-SECURITY

DATACRYPTOR® GIG ETHERNET
SECURITY POLICY

Figure 4-8 1600X437, Rev. 01 Rear





Figure 4-9 1600x437, Rev. 01 Top



The tamper evident labels shall only be applied at the Thales facility. Tamper evident labels are not available for order or replacement from Thales.

Three tamper evident labels are required to be visible and undamaged for each module to be operated in a FIPS approved mode of operation. They must be in the positions shown in Figure 4-8 and Figure 4-9.

DATACRYPTOR® GIG ETHERNET

SECURITY POLICY

4.1.4 1600X437, Rev. 02 Hardware

Figure 4-10 1600X437, Rev. 02 Front






Figure 4-11 1600X437, Rev. 02 Rear



THALES e-SECURITY

DATACRYPTOR® GIG ETHERNET
SECURITY POLICY

Figure 4-12 1600x437, Rev. 02 Top



The tamper evident labels shall only be applied at the Thales facility. Tamper evident labels are not available for order or replacement from Thales.

Two tamper evident labels are required to be visible and undamaged for each module to be operated in a FIPS approved mode of operation. They must be in the positions shown in Figure 4-12.

5. MITIGATION OF OTHER ATTACKS POLICY

None.

THALES e-SECURITY

DATACRYPTOR® GIG ETHERNET
SECURITY POLICY

ACRONYMS AND ABBREVIATIONS

| Acronym | Definition |
|---------|------------------------------------------------|
| AES | Advanced Encryption Standard |
| ANSI | American National Standards Institute |
| CA | Certification Authority |
| CTS | Cipher Text Stealing |
| DEK | Data Encryption Key |
| DSA | Digital Signature Algorithm |
| EDC | Error Detection Code |
| FIPS | Federal Information Processing Standards |
| ITU | International Telecommunications Union |
| KAT | Know Answer Test |
| KEK | Key Encryption Key |
| LAN | Local Area Network |
| MAC | Media Access Control |
| NIST | National Institute of Standards and Technology |
| PPP | Point-to-Point |
| PRNG | Pseudo Random Number Generator |
| PSU | Power Supply Unit |
| RIP | Routing Information Protocol |
| RNG | Random Number Generator |
| SDH | Synchronous Digital Hierarchy |
| SFP | Small Form Factor Pluggable |
| SHA-1 | Secure Hash Algorithm |
| SNMP | Simple Network Management Protocol |
| VLAN | Virtual LAN |
| XFP | 10 Gigabit Small Form Factor Pluggable |

DATACRYPTOR® GIG ETHERNET SECURITY POLICY

REFERENCES

1. FIPS 140-2 Security Requirements for Cryptographic Modules, Federal Information Processing Standards Publication, 25th May 2001. Including Change Notices 2,3,4: 12/03/2002
Available from the NIST web site: <http://www.nist.gov/cmvp>
2. FIPS 186-2 Digital Signature Standard, Federal Information Processing Standards Publication, 27th January 2000. Including Change Notice 1: 5th October 2001.
Available from the NIST web site: <http://www.nist.gov/cmvp>
3. Datacryptor® Gig Ethernet User Manual, 1270A427, Issue 8 June 2008.
Available from Thales e-Security.
4. AES Keywrap Specification Nov 2001 NIST

----- END OF DOCUMENT -----